

SK LT Sanitizer

ENVIROCHEM

425 Whitehead Avenue
South River, NJ 08882
Phone—732-238-6700
Fax— 732-238-5590

GENERAL DESCRIPTION:SK LT SANITIZER is a sodium hypochlorite based sanitizer providing sanitation in dishmachines used in commercial and institutional foodservice operations. SK LT SANITIZER is a buffered (high level of free alkali) product which enhances its stability when compared to other chlorine products. Chlorine content aids in stain removal on plastic and china tableware. The chlorine content also provides soil removal in wash cycle. SK LT SANITIZER is safe for use on stainless steel, glass, china, porcelain and plastic. Not recommended for use on sterling silver, silver plate or other corrodible soft metals.

PROPERTIES:

Chemical composition . . . Buffered sodium hypochlorite
Appearance. Clear yellow liquid
pH of 1% solution 10.0
Specific Gravity 1.104 (9.16 lbs./gal)
Caustic Present
Solubility Complete and Fast
Available Chlorine 6% (600 ppm in 1% solution)
Stability 180 days @ Ambient Temperature
Metal Safety Not safe for use on corrodible soft metals

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label.

Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

INSTRUCTIONS FOR USE:

LOW TEMPERATURE DISHMACHINE SANITIZER

to be automatically injected during beginning of "final rinse" portion of machine operating cycle. Use approximately 4 to 7 cc's per gallon of water to achieve a level of approximately 50 to 100 ppm available chlorine as measured with Chlorine Test Kit. Consult local sanitation regulations for specific requirements.

MANUAL SANITIZING RINSE FOR GLASSES, DISHES AND UTENSILS

1. Scrape and pre-flush articles to be washed.
2. Wash with recommended Envirochem products.
3. Rinse with potable water.
4. Sanitize by immersion in LT SANITIZER solution using approximately 1 ounce to each 4 gallons of water (100 ppm available chlorine). Immerse all utensils for at least two minutes or for contact time specified by governing sanitation regulations. Test periodically with Chlorine Test Kit. When solution depreciates to 50 ppm available chlorine, discard.
5. Air dry on clean drain board.

SPECIAL APPLICATIONS FOR LOW TEMP SANITIZER

1. DEODORIZING NON-FOOD CONTACT SURFACES - Use 2 ounces LT SANITIZER in one gallon of water (approximately 600 ppm available chlorine). Spray or rinse odor problem area. If applied to food contact surfaces, rinse with potable water after application.

For assistance and recommendations for sanitizing other equipment, consult your Representative.

HANDLING PRECAUTIONS

CAUTION: WARNING. KEEP OUT OF REACH OF CHILDREN

Contains chlorine. Contact with skin and eyes may cause severe irritation. Harmful if swallowed. Flood with water if splashed in eyes. Flush with water for 15 minutes and consult a physician immediately. If ingested, drink large amounts of milk, milk of magnesia or gelatin, or if these are not available, drink large amounts of water.

PACKAGING:

- 5 gal plastic pail - 46 lbs. net / 49 lbs. gross
- 4 X 1 gal. bottles/ctn—38 lbs. net / 40 lbs. gross